

Filters check valves



Filters

Description Filter made of hot-pressed brass with replaceable stainless steel sieve for direct installation in domestic drinking water installations.

Technical specifications **Operating pressure**
Up to size G1: 16 bar
From size G1¼: 10 bar

Connections
See ordering table





Check valve

Check valve made of brass for direct installation in domestic drinking water installations. Also suitable as a gravity brake. Nylon valve, seal seat NBR, spring stainless steel.

Operating temperature range
Medium: Max. 110 °C

Operating pressure
Up to size G1: 12 bar
Size G1¼ and greater: 10 bar

Connections
See ordering table

DG: G	PG			Part no.	Price €
Filter G³/₈	2	1	-	42580	
Filter G¹/₂	2	1	-	42581	
Filter G³/₄	2	1	-	42582	
Filter G1	2	1	-	42583	
Filter G1¼	2	1	-	42584	
Filter G1½	2	1	-	42585	
Filter G2	2	1	-	42586	
Check valve G³/₈ – DN 10	2	1	-	42540	
Check valve G¹/₂ – DN 15	2	1	-	42541	
Check valve G³/₄ – DN 20	2	1	-	42542	
Check valve G1 – DN 25	2	1	-	42543	
Check valve G1¼ – DN 32	2	1	-	42544	
Check valve G1½ – DN 40	2	1	-	42545	
Check valve G2 – DN 50	2	1	-	42546	