

Automatic fuel oil de-aerator FloCo-Top-2








Benefits

- Multiple filtration for maximum separation of dirt particles
- Backflow preventer with integrated pressure relief towards the tank
- Drain system for fast and clean filter change
- Bypass valve for easy and clean burner hose replacement
- Dual float safety system keeps oil foam from escaping
- Vacuum gauge indicates when it is time to replace the filter
- Pipe connection via universal screw connection or standard screw connection
- Reduced height facilitates installation if mounting space is limited
- Easy installation with click system and AFRISO universal screw connection or standard screw connection
- Materials resistant to biofuel and biodiesel mixtures with max. 20 % FAME
- PROOFED BARRIER if installed with vent hose
- Watertight up to 10 m water column - ideal for use in flood hazard areas

Application

For single-line systems with return line in oil consuming systems for continuous de-aeration. Suitable for the following media: fuel oil EL (DIN 51603-1) and diesel fuel (EN 590) as well as biofuel and biodiesel (EN 14214) with max. 20 % FAME. Also for use in flood hazard areas. Flo-Co-TOP-2 can be installed in any system. Multiple filtration is recommended for burners with an oil consumption of < 20 l/h while larger systems should be operated with single filtration.

Versions

		Filter	Filter surface	Part no.
	Fuel oil de-aerators FloCo-Top-2KM MC-7	Opticlean MC-7 short, 5–20 µm	700 cm ²	70112
	Fuel oil de-aerators FloCo-Top-2KM MS-5	Opticlean MS-5 short, 20–35 µm	500 cm ²	70134
	Fuel oil de-aerators FloCo-Top-2KM Optimum MC-18	Opticlean MC-18 long, 5–20 µm	1,850 cm ²	70114
	Fuel oil de-aerators FloCo-Top-2KM Optimum Si	Sintered plastic sieve Optimum, 50–70 µm	200 cm ²	70115
	Fuel oil de-aerators FloCo-Top-2KM Si	Sintered plastic sieve short, 50–70 µm	115 cm ²	70110
				Blue part no. = in-stock items
				Part no.
Pressure gauges -0.7/+0.9 bar				70030
Holder for FloCo-Top-2 series				70127
				Blue part no. = in-stock items

Description

Automatic fuel oil de-aerator, safety version, with integrated filter, shut-off valve and vacuum gauge. Housing with changeover valve for multiple filtration as well as backflow preventer with integrated pressure relief towards the tank. Compact de-aerator hood made of transparent plastic with dual float safety system to keep oil foam from escaping via the de-aerator opening. The vent hose is connected at the side in an unobtrusive way. For venting, the oil is guided via the float chamber and can then be added directly to the flow or it can be filtered again by switching a valve. In the case of multiple filtration, the return oil increases the flow rate so that the filter bowl is permanently filled with de-aerated oil. In service mode, the vacuum gauge indicates the pump vacuum. The shut-off valve can be closed to check the suction capacity of the burner pump. Increased vacuum provides information on the degree of pollution of the filter. The drain unit ensures that replacing the filter is easy and clean: Connect the hose, open the drain valve, loosen the union nut of the filter cup and drain the oil in a controlled way. When the burner hose needs to be replaced, it is sufficient to open a bypass valve so that the oil is drained from the float chamber via the filter cup and the drain unit. Water-tight up to 10 m water column.



Technical specifications

Connection burner end

G $\frac{3}{4}$ male with 60° cone for burner hoses

Connection tank

G $\frac{3}{4}$ female

Nozzle capacity

Max. 100 l/h

Return flow

Max. 120 l/h

Separating capacity air/gas

> 4 l/h

Mounting position

Float housing vertical to the top

Operating temperature range

Medium: Max. 60 °C

Ambient: Max. 60 °C

Operating overpressure

Max. 0.7 bar

Corresponds to static oil column of approx. 8 m

Test pressure

6 bar

Vacuum gauge

Range: -0.7/+0.9 bar

Dimensions (W x H x D)

183 x 254 x 103 mm

183 x 348 x 103 mm

Material

Housing: Zinc die cast

De-aerator hood: Transparent plastic

Filter cup: Transparent plastic

Test

TÜV-tested (S 133 2013 E2)

Approval for construction products

Conformity certificate (ÜHP) as per EN 12514-2

Scope of delivery

- Fuel oil de-aerators
- Universal screw connections for pipes \varnothing 6/8/10 mm
- Bracket with mounting material
- Cover for connection of the vent hose
- Drain hose