


## Tank protection package AK-S for fuel oil and diesel



### Benefits

- Inner lining package for standardised cylindrical tanks (EN/DIN) with all mounting accessories and vacuum type leak detector Eurovac
- Materials resistant to biofuel and biodiesel mixtures with max. 20 % FAME
- Tank protection packages for rectangular and spherical tanks on request
- Customised training seminars on installation of inner linings and leak detectors possible

### Application

For fuel oil EL (DIN 51603-1), diesel fuel (EN 590) and biofuel as well as biodiesel with up to 20 % FAME.

### Versions

Tank volume	Part no.
3,000 l	43901.003
5,000 l	43901.005
7,000 l	43901.007
10,000 l	43901.010
13,000 l	43901.013
15,000 l	43901.015
16,000 l	43901.016
20,000 l	43901.020
25,000 l	43901.025
30,000 l	43901.030
40,000 l	43901.040
50,000 l	43901.050

Blue part no. = in-stock items



Tank volume	Part no.
60,000 l	43901.060
80,000 l	43901.080
100,000 l	43901.100

Blue part no. = in-stock items

## Description

Tank protection package with Technical Approval of the German Institute for Civil Engineering (DIBt) for cylindrical tanks. Enquire for rectangular and spherical tanks.

## Technical specifications

### Approval for construction products

DIBt: Z-65.30-162, EN 13160-7

### Scope of delivery

- Leak protection lining according to standard or made to size
- Vacuum type leak detector Eurovac
- Front wall lining made of fleece LSV2
- Intermediate layer made of fleece
- Mipoplast plate 800 x 800 mm
- Condensate bar triple 4/6 mm
- Liquid barrier 4/6 mm
- Angled nipple short 4/6 mm
- Angled nipple long 4/6 mm
- PVC suction line 3 x 6 mm perforated and not perforated
- Fastening ring 500 mm or 600 mm
- Hose connector 4 or 6 mm
- T piece hose connection 4 or 6 mm
- Hose connector kit ND4/6 G $\frac{3}{8}$  x G $\frac{3}{8}$
- Warning sign with holder and felt overshoes